



**4x 10/100M
PoE supported ports**

**2x 10/100M
communication ports**

Main Features

- **4x 10/100M Ethernet ports with PoE support**
- **2x 10/100M Ethernet ports**
- IEEE802.3af PoE protocol support
- Maximum 15.4W power output per interface
- 60W maximum combined power output
- Automatic detection of Powered Devices
- Flow control for Full Duplex operation

Technical Specifications

Network Connections:

Port 1-4: 10/100M with PoE
 Port 5-6 (WAN): 10/100M
 Transmission distance: ~100m (max.)
 Transmission medium: CAT5/5e/6 standard network cable

Network Switch:

Network Standards: IEEE802.3/10 BASE-T Ethernet
 IEEE802.3/100 BASE-TX Ethernet
 IEEE802.3x Flow Control
 Maximum Frame Size: 1528 Bytes
 MAC address list: 2K
 PoE standard: IEEE802.3af & IEEE802.3at

Power over Ethernet:

PoE Power Supply Type: End-span (1/2+, 3/6-)

Power Supply:

Power Adapter Voltage: Input: 180-240V AC at 50/60Hz
 Output: DC 48V
 Power Consumption: 75W

Physical Specifications:

Dimensions (WxDxH): 156mm x 139,6 mm x 29,6 mm
 Working Temperature: 0°C ~ 40°C (5%-95%)
 Storage Temperature: 20°C ~ 70°C
 Weight: 780g